

iQ300, Gas hob, 60 cm, Black EN6B6HB90



The gas hob with front-mounted controls.

- ✓ This wok burner with up to 3.3 kW of power (depending on gas type) is ideal for a wide variety of foods, even in large quantities.
- ✓ High-quality materials and workmanship – continuous cast-iron pan supports.
- ✓ Biomethane ready – Power your gas hob with renewable biomethane gas.
- ✓ The sword knob combines highest ease of use with modern design.
- ✓ Extremely heat-resistant and easy to clean – the modern hard glass surface.

Features

Technical Data

Product name/family : gas hob w integrated controls

Construction type : Built-in

Energy input : Gas

Total number of positions that can be used at the same time : 4

Type of control setting devices : sword knobs

Min. required niche size for installation (HxWxD) : 45 x 560-562 x 480-492 mm

Width of the appliance : 590 mm

Dimensions of the packed product (HxWxD) : 141 x 651 x 578 mm

Net weight : 14.6 kg

Gross weight : 14.6 kg

Residual heat indicator : no

Location of control panel : Hob front

Basic surface material : Tempered glass

Color of surface : Black

Color of frame : Black

Length electrical supply cord : 100 cm

EAN code : 4242003845677

Gas connection rating : 7800 W

Fuse protection : 3 A

Voltage : 220-240 V

Frequency : 50; 60 Hz



4 242003 845677

iQ300, Gas hob, 60 cm, Black EN6B6HB90

Features

Design

- Tempered glass hob surface, black
- For a flush or slightly raised built-in solution.: install the hob either flush or slightly raised on the worktop
- Cast iron pan supports separable

Usage convenience

- Sword control knobs: easily access knobs in front with strong grip for effortless turning.
- 1-handed ignition via control knobs: just push and turn the knob to ignite the flame.

Burners and power

- 4 Gas burners
- Left front: Standard burner up to 1.75 KW (depending on gas type)
- Left rear: Standard burner up to 1.75 KW (depending on gas type)
- Right rear: Wok burner up to 3.3 KW (depending on gas type)
- Right front: Economy burner up to 1 KW (depending on gas type)

Safety

- Flame failure safety device: prevents unwanted gas flow when flame goes out.

Installation (gas types & measurements)

- Usable for: Nat gas L/LL G25/20mbar(DE)
- NG H/E 20mbar, E+ 20/25mbar Natural gas H 25 mbar (HU) Natural gas L 25 mbar (NL) Liquid gas G30,31 28-30/37mbar Liquid gas G30 37 mbar (PL) Liquid gas 50 mbar
- Preset for natural gas (20mbar)
- Nozzle set for Liquid gas nozzles (28-30/37mbar) included. Nozzles for all other gas types can be ordered via the customer service. For nozzle change, please contact the customer service.
- Dimensions of the product (HxWxD mm): 56 x 590 x 520
- Required niche size for installation (HxWxD mm) : 45 x 560 x (480 - 492)
- Min. worktop thickness: 30 mm
- Power cord: 1 m
- Connected load: 7.8 KW

iQ300, Gas hob, 60 cm, Black
EN6B6HB90

Dimensioned drawings

