

iQ500, canopy cooker hood, 52 cm, Stainless steel LB57574



The powerful canopy cooker hood is concealed above the cooktop.

- ✓ Optimal visibility and atmosphere when cooking - LED light.
- ✓ Intensive setting revert - Peak performance when steam escapes, and an automatic revert after a few minutes.

Features

Technical Data

Typology : Built-in/Built-under
 Approval certificates : CE, VDE
 Length electrical supply cord : 150 cm
 Required niche size for installation (HxWxD) : 418mm x 496.0mm x 264mm mm
 Minimum distance above an electric hob : 500 mm
 Minimum distance above a gas hob : 650 mm
 Net weight : 7.2 kg
 Type of control : Electronic
 Maximum output air extraction : 560 m³/h
 Boost position output recirculating : 581 m³/h
 Maximum output recirculating air : 533 m³/h
 Boost position air extraction : 615 m³/h
 Number of lights : 2
 Noise level : 67 dB(A) re 1 pW
 Diameter of air outlet : 120 / 150 mm
 Grease filter material : Washable aluminium
 EAN code : 4242003681497
 Connection Rating : 252 W
 Fuse protection : 3 A
 Voltage : 220-240 V
 Frequency : 50 Hz
 Plug type : GARDY plug w/ earthing
 Installation typology : Built-in



iQ500, canopy cooker hood, 52 cm, Stainless steel LB57574

Features

- Energy Efficiency Class: C (at a range of energy efficiency classes from A+++ to D)
- Average Energy Consumption: 90.2 kWh/year
- Blower Efficiency Class: C*
- Lighting Efficiency Class: A
- Grease Filtering Efficiency Class: D
- Noise min./max. Normal Level: 50/67 dB

Variant:

Design:

Technical information

Environment and safety:

Comfort:

Measures:

- For installation in a kitchen cabinet
- Suitable for ducted or re-circulated extraction
- For recirculated extraction standard recirculation kit or Clean Air Plus recirculation kit (accessory) needed
- RimVentilation
- Filter cover stainless steel
- Metal grease filter, dishwasher safe
- 2 x LED spot 1W
- Light Intensity: 244 lux
- Colour Temperature: 4000 K
- Electronic controls
- Push button controls with Electronic display
- 3 speeds plus intensive setting
- Automatic revert setting, 6 minutes
- Twin channel high performance fan motor
- Extraction rate according to EN 61591 ø 15 cm:
 - max. Normal use: 560 m³/h
 - Intensive: 615 m³/h
- Noise level according to EN 60704-2-13 exhaust air:
 - Max. normal use: 67 dB(A) re 1 pW
 - Intensive: 70 dB(A) re 1 pW
- Max. extraction rate: 615 m³/h
- Dimensions (HxWxD): 418 x 520 x 300 mm
- Built-in dimensions (HxWxD): 418 x 496 x 264 mm
- 120 or 150 mm diameter pipe
- Power rating: 252 W
- with one-way flap
- With the Clean Air Plus recirculation kit (available as optional accessory) your appliances reaches:
 - Extraction rate in recirculation mode: Max. normal use: 533 m³/h
 - Intensive: 581 m³/h
 - Noise level in recirculation mode: Max. normal use: 72 dB(A) re 1 pW
 - Intensive: 74 dB(A) re 1 pW

* In accordance with the EU-Regulation No 65/2014

iQ500, canopy cooker hood, 52 cm,
Stainless steel
LB57574

Dimensioned drawings

