

## iQ700, canopy cooker hood, 70 cm, clear glass white printed LB79585M

A++



The powerful canopy cooker hood is concealed above the cooktop.

- ✓ iQdrive motor - The quiet, high-performance motor ensures efficient removal of odours and steam.
- ✓ Optimal visibility and atmosphere when cooking - LED light.
- ✓ Pleasantly quiet - motor
- ✓ Intensive setting revert - Peak performance when steam escapes, and an automatic revert after a few minutes.

### Features

#### Technical Data

Typology : Built-in/Built-under  
 Approval certificates : CE, VDE  
 Length electrical supply cord : 100 cm  
 Required niche size for installation (HxWxD) : 418mm x 676.0mm x 264mm mm  
 Minimum distance above an electric hob : 500 mm  
 Minimum distance above a gas hob : 650 mm  
 Net weight : 9.1 kg  
 Type of control : Electronic  
 Maximum output air extraction : 575 m<sup>3</sup>/h  
 Boost position output recirculating : 722 m<sup>3</sup>/h  
 Maximum output recirculating air : 533 m<sup>3</sup>/h  
 Boost position air extraction : 775 m<sup>3</sup>/h  
 Number of lights : 2  
 Noise level : 64 dB(A) re 1 pW  
 Diameter of air outlet : 120 / 150 mm  
 Grease filter material : Washable aluminium  
 EAN code : 4242003845523  
 Connection Rating : 172 W  
 Fuse protection : 3 A  
 Voltage : 220-240 V  
 Frequency : 50 Hz  
 Plug type : Gardy plug w/ earthing  
 Installation typology : Built-in

### Optional accessories

LZ55651	Standard odor filter (replacement)
LZ11IXC16	Clean Air Plus recirc. kit external
LZ11IXB16	Clean Air Plus odor filter (replacement)
LZ11ITD11	Long Life recirculation kit external



4 242003 845523

## iQ700, canopy cooker hood, 70 cm, clear glass white printed LB79585M

### Features

- Energy Efficiency Class: A++ (at a range of energy efficiency classes from A+++ to D)
- Average Energy Consumption: 30.3 kWh/year
- Blower Efficiency Class: A\*
- Lighting Efficiency Class: A
- Grease Filtering Efficiency Class: D
- Noise min./max. Normal Level: 46/64 dB

#### Variant:

#### Design:

#### Technical information

#### Environment and safety:

#### Comfort:

#### Measures:

- For installation in a kitchen cabinet
- Suitable for ducted or re-circulated extraction
- For recirculated extraction standard recirculation kit or Clean Air Plus recirculation kit (accessory) needed
- RimVentilation
- Filter cover glass
- Glass plate clear glass white printed
- Metal grease filter, dishwasher safe
- Saturation indicator for grease filter
- 2 x LED spot 1W
- Light dimmer function
- Light Intensity: 244 lux
- Colour Temperature: 4000 K
- Electronic controls
- Push button controls with Electronic display
- 3 speeds plus intensive setting
- Automatic revert setting, 6 minutes
- 30 min.
- Interval operation
- iQ-drive - efficient BLDC-technology
- Extraction rate according to EN 61591 ø 15 cm:
- max. Normal use: 575 m<sup>3</sup>/h
- Intensive: 775 m<sup>3</sup>/h
- Noise level according to EN 60704-2-13 exhaust air:
- Max. normal use: 64 dB(A) re 1 pW
- Intensive: 70 dB(A) re 1 pW
- Max. extraction rate: 775 m<sup>3</sup>/h
- Dimensions (HxWxD): 418 x 700 x 300 mm
- Built-in dimensions (HxWxD): 418 x 676 x 264 mm
- 120 or 150 mm diameter pipe
- Power rating: 172 W
- with one-way flap
- With the Clean Air Plus recirculation kit (available as optional accessory) your appliances reaches:
- Extraction rate in recirculation mode: Max. normal use: 533 m<sup>3</sup>/h
- Intensive: 722 m<sup>3</sup>/h
- Noise level in recirculation mode: Max. normal use: 71 dB(A) re 1 pW
- Intensive: 77 dB(A) re 1 pW

#### Technical information

\* In accordance with the EU-Regulation No 65/2014

iQ700, canopy cooker hood, 70 cm,  
clear glass white printed  
LB79585M

Dimensioned drawings

