

## iQ500, wall-mounted cooker hood, 60 cm, Stainless steel LC67BHP50



The powerful wall hood convinces with a high extraction rate and an outstanding design.

- ✓ iQdrive motor - The quiet, high-performance motor ensures efficient removal of odours and steam.
- ✓ Optimal visibility and atmosphere when cooking - LED light.
- ✓ Extremely quiet – The quiet hood that keeps the calm your kitchen.
- ✓ Innovative dual air inlet design, the fume is nowhere to hide.
- ✓ The power level and the LED light can be selected directly – touchControl

### Features

#### Technical Data

Typology : Wall-mounted  
 Length electrical supply cord : 130 cm  
 Height of the chimney : 582-908/568-1018 mm  
 Height of the appliance : 614-954/614-1064 mm  
 Minimum distance above an electric hob : 550 mm  
 Minimum distance above a gas hob : 650 mm  
 Net weight : 20.2 kg  
 Type of control : Electronic  
 Number of speed settings : 3-stage + 2 intensive  
 Maximum output air extraction : 416 m<sup>3</sup>/h  
 Boost position output recirculating : 409 m<sup>3</sup>/h  
 Maximum output recirculating air : 330 m<sup>3</sup>/h  
 Boost position air extraction : 674 m<sup>3</sup>/h  
 Number of lights : 2  
 Noise level : 60 dB(A) re 1 pW  
 Diameter of air outlet : 120 / 150 mm  
 Grease filter material : Washable aluminium  
 EAN code : 4242003831731  
 Connection Rating : 143 W  
 Fuse protection : 10 A  
 Voltage : 220-240 V  
 Frequency : 50; 60 Hz  
 Plug type : Gardy plug w/ earthing  
 Installation typology : Wall-mounted

### Optional accessories

LZ31XXB16	Clean Air Plus odor filter (replacement)
LZ31CXB14	Clean Air Standard odor filter (repl.)
LZ12350	Chimney extension 1500 mm
LZ12250	Chimney extension 1000 mm
LZ11FXD51	Long Life recirculation kit external
LZ11FXC56	Clean Air Plus recirc. kit external
LZ11CXI16	Clean Air Plus recirculation kit
LZ11CBI14	Clean Air Standard recirculation kit
LZ10FXJ05	Long Life recirculation kit



## iQ500, wall-mounted cooker hood, 60 cm, Stainless steel LC67BHP50

### Features

- Energy Efficiency Class: A (at a range of energy efficiency classes from A+++ to D)
- Average Energy Consumption: 36.1 kWh/year
- Blower Efficiency Class: A\*
- Lighting Efficiency Class: A
- Grease Filtering Efficiency Class: B
- Noise min./max. Normal Level: 47/60 dB

#### Variant:

#### Design:

#### Technical information

#### Performance

#### Power:

#### Environment and safety:

#### Comfort:

#### Measures:

#### Technical information

- Wall Hood stainless steel
- 60 cm wide
- 60 cm Chimney hood, stainless steel
- Suitable for ducted or re-circulated extraction
- For recirculated extraction standard recirculation kit or Clean Air Plus recirculation kit (accessory) needed
- Wall mounted hood
- wall fixing system
- touchControl
- Electronic controls
- touchControl with 7-segment display
- 3 speeds plus 2 intensive via touchControl
- Electronic controls via touchControl with 7-segment display
- touchControl (3 speeds plus 2 intensive) with 7-segment display
- 3 speeds plus 2 intensive
- Automatic revert setting, 6 minutes
- Automatic 10 minutes after running
- Boost function
- easy to clean Innerframe
- Light dimmer function
- softLight
- Efficient BLDC-technology
- 2 x 1,5 W LED
- Light Intensity: 267 lux
- Colour Temperature: 3500 K
- Saturation indicator for grease filter and odor filter
- Cassette with alu frame
- Metal grease filter, dishwasher safe
- Extraction rate according to EN 61591 ø 15 cm:
  - max. Normal use 417 m<sup>3</sup>/h
  - Intensive 674 m<sup>3</sup>/h
- Extraction rate exhaust air according to EN 61591 max. 674 m<sup>3</sup>/h
- Extraction rate according to EN 61591 ø 15 cm:
  - max. Normal use 417 m<sup>3</sup>/h
  - Intensive 674 m<sup>3</sup>/h
- Extraction rate exhaust air according to EN 61591:

- max. normal use 417 m<sup>3</sup>/h, intensive 674 m<sup>3</sup>/h
- Dimensions recirculating with CleanAir Plus recirculation kit (HxWxD):
  - 689 x 598 x 500 mm - mounting with outer chimney
  - 795-1139 x 598 x 500 mm - mounting with telescopic chimney
- Noise level according to EN 60704-2-13 at max. normal use exhaust air: Noise, max. speed in normal use: 60 dB dB(A) re 1 pW
- Noise level according to EN 60704-2-13 exhaust air:
  - Max. normal use: 60 dB(A) re 1 pW
  - Intensive: 71 dB(A) re 1 pW
- Diameter pipe Ø 150 mm (Ø 120 mm enclosed)
- with one-way flap
- Max. extraction rate: 674 m<sup>3</sup>/h
- Dimensions exhaust air (HxWxD): 614-954 x 598 x 500 mm
- Dimensions recirculating (HxWxD): 614-1064 x 598 x 500 mm
- Power rating: 143 W
- Electrical cable length 1.3 m
- Voltage: 220 - 240 V
- With the Clean Air Plus recirculation kit (available as optional accessory) your appliances reaches:
  - Extraction rate in recirculation mode: Max. normal use: 330 m<sup>3</sup>/h
  - Intensive: 409 m<sup>3</sup>/h
- Noise level in recirculation mode: Max. normal use: 67 dB(A) re 1 pW
- Intensive: 71 dB(A) re 1 pW

\* In accordance with the EU-Regulation No 65/2014

iQ500, wall-mounted cooker hood, 60 cm, Stainless steel  
LC67BHP50

Dimensioned drawings

