


iQ300, wall-mounted cooker hood, 60 cm, Black LC67KEM60



B



Angled extractor hood with outstanding design and high extraction rate for a powerful performance.

- ✓ Optimal visibility and atmosphere when cooking - LED light.
- ✓ Extremely quiet – The quiet hood that keeps the calm your kitchen.
- ✓ The power level and the LED light can be selected directly – touchControl
- ✓ Intensive setting with automatic after revert setting
- ✓ Intensive setting revert - Peak performance when steam escapes, and an automatic revert after a few minutes.

Features

Technical Data

Typology : Wall-mounted
 Approval certificates : CE, VDE
 Length electrical supply cord : 130 cm
 Height of the chimney : 484-770/554-830 mm
 Height of product, without chimney : 296 mm
 Minimum distance above an electric hob : 450 mm
 Minimum distance above a gas hob : 650 mm
 Net weight : 13.8 kg
 Type of control : Electronic
 Maximum output air extraction : 399 m³/h
 Boost position output recirculating : 474 m³/h
 Maximum output recirculating air : 349 m³/h
 Boost position air extraction : 669 m³/h
 Number of lights : 2
 Noise level : 60 dB(A) re 1 pW
 Diameter of air outlet : 120 / 150 mm
 Grease filter material : Washable aluminium
 EAN code : 4242003862612
 Connection Rating : 255 W
 Fuse protection : 10 A
 Voltage : 220-240 V
 Frequency : 50; 60 Hz
 Plug type : Gardy plug w/ earthing
 Installation typology : Wall-mounted

Optional accessories

LZ31XXB16	Clean Air Plus odor filter (replacement)
LZ12350	Chimney extension 1500 mm
LZ12250	Chimney extension 1000 mm
LZ11FXC56	Clean Air Plus recirc. kit external
LZ11EKU11	Standard recirculation kit
LZ11DXI16	Clean Air Plus recirculation kit
LZ10FXJ00	Long Life recirculation kit
LZ00XXP00	Long Life odor filter (replacement)



iQ300, wall-mounted cooker hood, 60 cm, Black LC67KEM60

Features

- Energy Efficiency Class: B (at a range of energy efficiency classes from A+++ to D)
- Average Energy Consumption: 59.4 kWh/year
- Blower Efficiency Class: B*
- Lighting Efficiency Class: A
- Grease Filtering Efficiency Class: C
- Noise min./max. Normal Level: 48/60 dB

Variant:

Design:

Technical information

Performance

Power:

Environment and safety:

Comfort:

Measures:

Technical information

- Inclined Hood black
- 60 cm Chimney hood, black
- 60 cm Chimney hood
- 60 cm wide
- Glass plate: clear glass black printed
-
- Suitable for ducted or re-circulated extraction
- For recirculated extraction standard recirculation kit or Clean Air Plus recirculation kit (accessory) needed
- Wall mounted hood
- touchControl
- Electronic controls
- Electronic control via touch control
- touchControl with Electronic display
- 3 speeds plus intensive setting via touchControl
- Electronic controls via touchControl with Electronic display
- touchControl (3 speeds plus intensive setting) with Electronic display
- 3 speeds plus intensive setting
- Automatic revert setting, 6 minutes
- Twin channel high performance fan motor
- Energy efficient capacitor motor
- 2 x 1,5 W LED
- Light Intensity: 130 lux
- Colour Temperature: 3500 K
- Metal grease filter, dishwasher safe
- 2 capture areas: front side and bottom side
- RimVentilation
- Filter cover glass
- Extraction rate according to EN 61591 ø 15 cm:
 - max. Normal use 399 m³/h
 - Intensive 669 m³/h
- Extraction rate exhaust air according to EN 61591:
 - max. normal use 399 m³/h, intensive 669 m³/h
- Noise level according to EN 60704-2-13 exhaust air:
 - Max. normal use: 60 dB(A) re 1 pW

- Intensive: 69 dB(A) re 1 pW
- Diameter pipe Ø 150 mm (Ø 120 mm enclosed)
- with one-way flap
- Max. extraction rate: 669 m³/h
- With the Clean Air Plus recirculation kit (available as optional accessory) your appliances reaches:
 - Extraction rate in recirculation mode: Max. normal use: 349 m³/h
 - Intensive: 474 m³/h
- Noise level in recirculation mode: Max. normal use: 69 dB(A) re 1 pW
- Intensive: 76 dB(A) re 1 pW
- Dimensions exhaust air (HxWxD): 780-1066 x 600 x 434 mm
- Dimensions recirculating (HxWxD): 850-1126 x 600 x 434 mm
- Dimensions recirculating with CleanAir Plus recirculation kit (HxWxD):
 - 956 x 600 x 434 mm - mounting with outer chimney
 - 1016-1306 x 600 x 434 mm - mounting with telescopic chimney
- Dimensions recirculating with cleanAir Plus recirculation kit (HxWxD);
 - 956 x 600 x 434 mm - mounting with outer chimney
 - 1016-1306 x 600 x 434 mm - mounting with telescopic chimney
- Dimensions recirculating with CleanAir Plus recirculation kit (HxWxD):
 - 956 x 600 x 434 mm - mounting with outer chimney
 - 1016-1306 x 600 x 434 mm - mounting with telescopic chimney
- 956 x 600 x 434 mm - mounting with outer chimney
- 1016-1306 x 600 x 434 mm - mounting with telescopic chimney
- Power rating: 255 W
- Electrical cable length 1.3 m
- Voltage: 220 - 240 V

* In accordance with the EU-Regulation No 65/2014

iQ300, wall-mounted cooker hood, 60 cm, Black
LC67KEM60

Dimensioned drawings

