


## iQ700, island cooker hood, 90 cm, Stainless steel LF91BUV50



A+

The island hood convinces with a very high extraction rate in a distinguished design that perfectly matches your kitchen.

- ✓ Powerful and quiet steam extraction – iQdrive motor
- ✓ Detects steam and odours to adjust the power level automatically – climateControl sensor with cookConnect system
- ✓ Access and control your hood, no matter where you are - Home Connect App (Android and iOS)
- ✓ Optimal visibility and atmosphere when cooking - LED light.
- ✓ Intensive setting starts automatically when you need it – Intensive setting with automatic revert.

### Features

#### Technical Data

Typology : Chimney  
 Approval certificates : CE, VDE  
 Length electrical supply cord (cm) : 130  
 Height of the chimney (mm) : 698-878/698-998  
 Height of product, without chimney (mm) : 46  
 Minimum distance above an electric hob : 550  
 Minimum distance above a gas hob : 650  
 Net weight (kg) : 31.627  
 Type of control : Electronic  
 Number of speed settings : 3-stage + 2 intensive  
 Maximum output air extraction (m³/h) : 598  
 Boost position output recirculating (m³/h) : 427.0  
 Maximum output recirculating air (m³/h) : 359  
 Boost position air extraction (m³/h) : 980  
 Number of lights : 4  
 Noise level (dB) : 62  
 Diameter of air outlet (mm) : 120 / 150  
 Grease filter material : Washable stainless steel  
 EAN code : 4242003832066  
 Connection Rating (W) : 266  
 Current (A) : 10  
 Voltage (V) : 220-240  
 Frequency (Hz) : 50; 60  
 Plug type : GARDY plug w/ earthing  
 Installation typology : Island

### Optional accessories

LZ53850 : Standard recirculation kit , LZ53451 : Standard odor filter (replacement) , LZ31XXB16 : Clean Air Plus odor filter (replacement) , LZ22FXD51 : Long Life recirculation kit external , LZ22CXC56 : Clean Air Plus recirc. kit external , LZ12530 : Extension for mounting kit 1000 mm , LZ12510 : Extension for mounting kit 500 mm , LZ12410 : Adapter for roof inclination front/back , LZ12385 : Chimney extension 1600 mm , LZ12310 : Adapter for roof inclination left/right , LZ12285 : Chimney extension 1100 mm , LZ00XPP00 : Long Life odor filter (replacement)



4 242003 832066

## iQ700, island cooker hood, 90 cm, Stainless steel LF91BUV50

### Features

- Energy Efficiency Class: A+ (at a range of energy efficiency classes from A+++ to D)
- Average Energy Consumption: 36.8 kWh/year
- Blower Efficiency Class: A\*
- Lighting Efficiency Class: A
- Grease Filtering Efficiency Class: B
- Noise min./max. Normal Level: 43/62 dB

#### Variant:

#### Design:

#### Technical information

#### Performance

#### Power:

#### Environment and safety:

#### Comfort:

#### Measures:

#### Technical information

- Island Hood stainless steel
- 90 cm wide
- 90 cm Island chimney hood, stainless steel
- Suitable for ducted or re-circulated extraction
- For recirculated extraction standard recirculation kit or Clean Air Plus recirculation kit (accessory) needed
- Ceiling mounted hood
- Cooktop-based hood control
- (with matching cooktop)
- Home Connect for connected home appliances and operation via smartphone or tablet (only in countries where Home Connect service is available)
- The Home Connect functionality can be extended by integrating numerous applications from external cooperation partners (partnerships)
- Voice Control enabled via popular voice assistants (only in countries where this service is available)
- fully automatic hood
- touchControl
- Electronic controls
- touchControl with 7-segment display
- 3 speeds plus 2 intensive via touchControl
- Electronic controls via touchControl with 7-segment display
- touchControl (3 speeds plus 2 intensive) with 7-segment display
- 3 speeds plus 2 intensive
- Automatic revert setting, 6 minutes
- Automatic 10 minutes after running
- Boost function
- easy to clean Innerframe
- Air quality sensor
- Light dimmer function
- softLight
- interval function: available via Home Connect
- silence function: available via Home Connect
- Efficient BLDC-technology

- 4 x 1,5 W LED
- Light Intensity: 411 lux
- Colour Temperature: 3500 K
- Saturation indicator for grease filter and odor filter
- Stainless steel filter covers, dishwasher safe
- Metal grease filter, dishwasher safe
- Extraction rate according to EN 61591 ø 15 cm:
  - max. Normal use 597 m³/h
  - Intensive 980 m³/h
- Extraction rate exhaust air according to EN 61591 max. 980 m³/h
- Extraction rate according to EN 61591 ø 15 cm:
  - max. Normal use 597 m³/h
  - Intensive 980 m³/h
- Extraction rate exhaust air according to EN 61591:
  - max. normal use 597 m³/h, intensive 980 m³/h
- Dimensions recirculating with CleanAir Plus recirculation kit (HxWxD): 812-1044 x 898 x 600 mm
- Additional noise insulation
- Noise level according to EN 60704-2-13 at max. normal use exhaust air: Noise, max. speed in normal use: 62 dB dB(A) re 1 pW
- Noise level according to EN 60704-2-13 exhaust air:
  - Max. normal use: 62 dB(A) re 1 pW
  - Intensive: 73 dB(A) re 1 pW
- Diameter pipe Ø 150 mm (Ø 120 mm enclosed)
- with one-way flap
- Max. extraction rate: 980 m³/h
- Dimensions exhaust air (HxWxD): 744-924 x 898 x 600 mm
- Dimensions recirculating (HxWxD): 744-1044 x 898 x 600 mm
- Power rating: 266 W
- Electrical cable length 1.3 m
- Voltage: 220 - 240 V
- With the Clean Air Plus recirculation kit (available as optional accessory) your appliances reaches:
  - Extraction rate in recirculation mode:
    - Max. normal use: 462 m³/h
    - Intensive: 561 m³/h
  - Noise level in recirculation mode:
    - Max. normal use: 68 dB(A) re 1 pW
    - Intensive: 72 dB(A) re 1 pW

\* In accordance with the EU-Regulation No 65/2014

**iQ700, island cooker hood, 90 cm,  
Stainless steel  
LF91BUV50**

Dimensioned drawings

