

iQ500, island cooker hood, 90 cm, Stainless steel LF97BCP50



The powerful island hood convinces with a high extraction rate and an outstanding design.

- ✓ iQdrive motor - The quiet, high-performance motor ensures efficient removal of odours and steam.
- ✓ Optimal visibility and atmosphere when cooking - LED light.
- ✓ Extremely quiet – The quiet hood that keeps the calm your kitchen.
- ✓ Innovative 5D annular suction design, omni-directional#capture smoke
- ✓ The power level and the LED light can be selected directly – touchControl

Features

Technical Data

Typology : Island/Ceiling
 Approval certificates : CE, VDE
 Length electrical supply cord : 130 cm
 Height of the chimney : 698-878/698-998 mm
 Height of product, without chimney : 46 mm
 Minimum distance above an electric hob : 550 mm
 Minimum distance above a gas hob : 650 mm
 Net weight : 28.2 kg
 Type of control : Electronic
 Number of speed settings : 3-stage + 2 intensive
 Maximum output air extraction : 444 m³/h
 Boost position output recirculating : 442 m³/h
 Maximum output recirculating air : 343 m³/h
 Boost position air extraction : 727 m³/h
 Number of lights : 4
 Noise level : 54 dB(A) re 1 pW
 Diameter of air outlet : 120 / 150 mm
 Grease filter material : Washable aluminium
 EAN code : 4242003832097
 Connection Rating : 146 W
 Fuse protection : 10 A
 Voltage : 220-240 V
 Frequency : 50; 60 Hz
 Plug type : Gardy plug w/ earthing
 Installation typology : Island

Optional accessories

LZ31XXB16	Clean Air Plus odor filter (replacement)
LZ22FXD51	Long Life recirculation kit external
LZ22CXC56	Clean Air Plus recirc. kit external
LZ22CB114	Clean Air Standard recirculation kit
LZ12530	Extension for mounting kit 1000 mm
LZ12510	Extension for mounting kit 500 mm
LZ12385	Chimney extension 1600 mm
LZ12310	Adapter for roof inclination left/right
LZ12285	Chimney extension 1100 mm
LZ00XXP00	Long Life odor filter (replacement)



iQ500, island cooker hood, 90 cm, Stainless steel LF97BCP50

Features

- Energy Efficiency Class: A (at a range of energy efficiency classes from A+++ to D)
- Average Energy Consumption: 31.9 kWh/year
- Blower Efficiency Class: A*
- Lighting Efficiency Class: A
- Grease Filtering Efficiency Class: B
- Noise min./max. Normal Level: 45/54 dB

Variant:

Design:

Technical information

Performance

Power:

Environment and safety:

Comfort:

Measures:

Technical information

- Island Hood stainless steel
- 90 cm wide
- 90 cm Island chimney hood, stainless steel
- Suitable for ducted or re-circulated extraction
- For recirculated extraction standard recirculation kit or Clean Air Plus recirculation kit (accessory) needed
- Ceiling mounted hood
- touchControl
- Electronic controls
- touchControl with 7-segment display
- 3 speeds plus 2 intensive via touchControl
- Electronic controls via touchControl with 7-segment display
- touchControl (3 speeds plus 2 intensive) with 7-segment display
- 3 speeds plus 2 intensive
- Automatic revert setting, 6 minutes
- Automatic 10 minutes after running
- Boost function
- easy to clean Innerframe
- Light dimmer function
- softLight
- Efficient BLDC-technology
- 4 x 1,5 W LED
- Light Intensity: 409 lux
- Colour Temperature: 3500 K
- Saturation indicator for grease filter and odor filter
- Cassette with alu frame
- Metal grease filter, dishwasher safe
- Extraction rate according to EN 61591 ø 15 cm:
 - max. Normal use 444 m³/h
 - Intensive 727 m³/h
- Extraction rate exhaust air according to EN 61591 max. 727 m³/h
- Extraction rate according to EN 61591 ø 15 cm:
 - max. Normal use 444 m³/h
 - Intensive 727 m³/h
- Extraction rate exhaust air according to EN 61591:
 - max. normal use 444 m³/h, intensive 727 m³/h

- Dimensions recirculating with CleanAir Plus recirculation kit (HxWxD): 812-1044 x 898 x 600 mm
- Additional noise insulation
- Noise level according to EN 60704-2-13 at max. normal use exhaust air: Noise, max. speed in normal use: 54 dB dB(A) re 1 pW
- Noise level according to EN 60704-2-13 exhaust air:
 - Max. normal use: 54 dB(A) re 1 pW
 - Intensive: 65 dB(A) re 1 pW
- Diameter pipe Ø 150 mm (Ø 120 mm enclosed)
- with one-way flap
- Max. extraction rate: 727 m³/h
- Dimensions exhaust air (HxWxD): 744-924 x 898 x 600 mm
- Dimensions recirculating (HxWxD): 744-1044 x 898 x 600 mm
- Power rating: 146 W
- Electrical cable length 1.3 m
- Voltage: 220 - 240 V
- With the Clean Air Plus recirculation kit (available as optional accessory) your appliances reaches:
 - Extraction rate in recirculation mode: Max. normal use: 343 m³/h
 - Intensive: 442 m³/h
 - Noise level in recirculation mode: Max. normal use: 66 dB(A) re 1 pW
 - Intensive: 70 dB(A) re 1 pW

* In accordance with the EU-Regulation No 65/2014

iQ500, island cooker hood, 90 cm,
Stainless steel
LF97BCP50

Dimensioned drawings

