

iQ500, Heat pump tumble dryer, 9 kg WQ45G209GB















Optional accessories

WZ27410 Stacking kit

WZ27400 Stacking kit with pull-out shelf

Outstanding laundry performance with A++, selfCleaning condenser and autoDry for gentle and even drying of your garments.

- ✓ selfCleaning condenser Removes lint to save you time and effort.
- ✓ AutoDry Gentle and precise drying that protects your clothes.
- ✓ Half load Optimise the duration of smaller loads with an accurate estimation of the selected programme.
- ✓ speedPack Save time with our fast and highly efficient dryers.
- ✓ Outdoor programme Dry your waterproof and outdoor clothing safely.

Feature

Technical Data

Construction type : Free-standing Removable work top : No Door hinge : Right

Length of electrical supply cord : 145.0 cm Height of removable worktop : 0 mm

Dimensions of the product: 842 x 598 x 613 mm

Net weight: 56.4 kg

Fluorinated greenhouse gases : No Type of refrigerant : R290 Hermetically sealed equipment : Yes

Quantity of fluorinated gases : 0.149 kg The quantity expressed in CO2 equivalent : 0.000 t

The quantity expressed in CO2 equivalent: 0.000 EAN code: 4242003913017

Connection rating: 800 W Fuse protection: 10 A Voltage: 220-240 V Frequency: 50 Hz

Approval certificates : CE, E17D UKCA marking, VDE Capacity cotton - NEW (2010/30/EC) : 9.0 kg

Energy efficiency rating: A++

Energy consumption electric dryer, full load - NEW (2010/30/EC): 2.05

kWh

Standard cotton programme time at full load: 176 min

Energy consumption electric dryer, partial load - NEW (2010/30/EC) :

1.25 kWh

Standard cotton programme time at partial load: 121 min

Weighted annual energy consumption, electric dryer - NEW (2010/30/

EC): 258.0 kWh/annum

Weighted programme time : 145 min

Average condensation efficiency full load (%) : 86 % Average condensation efficiency partial load (%) : 86 %

Weighted condensation efficiency (%): 86 %





iQ500, Heat pump tumble dryer, 9 kg WQ45G209GB

Features

Performance

- Energy Efficiency Class¹: A++
- Energy²: 258 kWh
- Capacity: 1 9 kg
- Programme time3: 176 min
- Noise level: 64 dB (A) re 1 pW
- Condensation efficiency class4: B
- Condensation efficiency⁵: 86 %

Programmes/functions

- Touch control buttons: Iron dry, Cupboard dry, Cupboard dry+, end time delay, less ironing, low heat, buzzer, Start / Reload / Pause, 24 h end time delay
- Standard programmes: cotton, easy care
- Special programmes: cotton, shirts, Cotton Eco, lingerie, towels, pillows, mixed fabrics, outdoor, rapid 40, blankets, easy-care, Woollens Finish, timed programmme warm

Key features

- Anti crease cycle 60 min at the end of the programme
- Fully electronic control dial for sensor and timed programmes
- \bullet Half Load option: optimises drying for smaller loads
- Sensitive drying: large softDry stainless steel drum system and revolution drying system
- AntiVibration design: for greater stability and quietness

Additional features

- Large LED display for remaining time and 24 hours time delay, programme progress indication and special functions
- NewValue door with cover glass, Liquid-chrome matt, black
- Load recommendation
- soft dial
- Heat pump technology with climate friendly cooling agent
- Drum interior light
- Container for condensed water
- Door hinge: right-hand
- Metal door catch
- Child lock
- End of cycle buzzer

.

Technical Information

- Slide-under installation
- Dimensions (H x W): 84.2 cm x 59.8 cm
- Appliance depth: 61.3 cm
- Appliance depth incl. door: 64.8 cm
- Appliance depth with open door: 109.6 cm
- ¹ At a range of energy efficiency classes from A+++ to D
- ² Energy consumption kWh per year, based on 160 drying cycles of the standard cotton programme at full and partial load, and the consumption of the low power modes
- ³ Programme time of the standard cotton programme at full load
- ⁴ On a condensation efficiency class scale from A to G
- ⁵ Weighted condensation efficiency for the standard cotton programme at full and partial load



iQ500, Heat pump tumble dryer, 9 kg WQ45G209GB

Dimensioned drawings 598 measurements in mm Measurements in mm 1096 648 842+15 613