

iQ700 Compact oven CB635GBS3, Stainless steel























Included accessories

1 x combination grid

1 x universal pan

Optional accessorie

HZ6BCA0 Cookbook HZ66X600 Decor list HZ327000 Baking stone The compact oven with a height of 45 cm offers modern baking and cooking convenience.

- ✓ coolStart: cook frozen food without preheating.
- ✓ TFT Display: good readability from any perspective.
- ✓ ecoClean: effortless cleaning thanks to a special coating of the rear
 wall that automatically absorbs grime.
- ✓ Energy efficiency class A+: For more efficient roasting and baking.
- ✓ cookControl Plus: guaranteed success for numerous dishes.

Feature

Technical Data

Color / Material Front : Stainless steel Built-in / Free-standing : Built-in Integrated Cleaning system : No

Required niche size for installation (HxWxD): 450-455 x 560-568 x

550

Dimensions of the product (mm): 455 x 594 x 548

Dimensions of the packed product (HxWxD) (mm) : $520 \times 710 \times 650$

Control Panel Material: Stainless steel

Door Material : Glass Net weight (kg) : 29.656 Usable volume of cavity (l) : 47

Cooking method:, 4D hot air, Bottom heat, Conventional heat, Deepfrozen food special, Full width grill, Half width grill, Hot Air-Eco, Hot air grilling, low temperature cooking, Pizza setting, pre-heating, warming

First cavity material: Enamelled Temperature control: electronic Number of interior lights: 1 Approval certificates: CE, VDE

Length electrical supply cord (cm): 150

EAN code : 4242003836477 Number of cavities (2010/30/EC) : 1 Energy efficiency class (2010/30/EC) : A+

Energy consumption per cycle conventional (2010/30/EC) : 0.73 Energy consumption per cycle forced air convection (2010/30/EC) :

0.61

Energy efficiency index (2010/30/EC): 81.3 Electrical connection rating (W): 2990

Current (A) : 13 Voltage (V) : 220-240 Frequency (Hz) : 50; 60

Plug type : Gardy plug w/ earthing





iQ700 Compact oven CB635GBS3, Stainless steel

Features

Type of oven / heating system:

- Compact oven with 13 heating methods: 4D hot air, Hotair eco,, Conventional heat, Conventional heat ECO, hotAir grilling, Full width grill, Half width grill, Pizza setting, coolStart, Bottom heat, Soft steaming, Plate warming setting, Hold warm setting, Independent oven interior light button, Halogen interior lighting
- Temperature range 30 °C 300 °C
- Cavity volume: 47 l

Design:

- Rotary Control
- Cavity inner surface: Enamel anthracite

Cleaning:

- ecoClean: coating of back panel
- Innerdoor main: Full glass inner door

Comfort

- 2,8"-TFT-color and text display with touch-control buttons
- Temperature proposal
- Actual temperature display
- heating-up control
- cookControl
- Sabbath setting
- softMove for gentle opening and closing of the oven door
- Supporting systems: Programs
- Number of automatic programmes: 10 PC
- electronic clock
- Rapid heating-up
- Halogen interior lighting, Independent oven interior light button
- Integral cooling fan
- Stainless-steel fan
- Info button
- Bar handle

Hook-in racks / rails

• Cavity with shelf support rails, Telescopic slide-out Accessory

Accessory:

• 1 x combination grid, 1 x universal pan

Environment and Safety:

- Low door temperature
- Child lock
- Automatic safety switch off
- Residual heat indicator
- Start-/Stop button
- door contact switch

Technical Info:


- Length of mains cable: 150 cm
- Total connected load electric: 2.99 KW
- Appliance dimension (hxwxd): 455 mm x 594 mm x 548 mm
- Niche dimension (hxwxd): 450 mm 455 mm x 560 mm 568 mm x 550 mm
- "Please reference the built-in dimensions provided in the installation drawing"
- Energy efficiency rating (acc. EU Nr. 65/2014): A+ (at a range of energy efficiency classes from A+++ to D)


• Energy consumption per cycle in conventional mode: 0.73 kwh Energy consumption per cycle in fan-forced convection mode: 0.61 kwh Number of cavities: 1 Heat source: electrical Cavity volume: 47





iQ700 Compact oven CB635GBS3, Stainless steel

Dimensioned drawings









If the compact appliance will be installed underneath a hob, the following worktop thicknesses (including substructure if necessary) must be taken into account.

Hob type	min. worktop thickness	
	fitted	flush
Induction hob	42 mm	43 mm
Full surface Induction hob	52 mm	53 mm
Gas hob	32 mm	43 mm
Electric hob	32 mm	35 mm