



CorePro LEDlinear MV



CorePro LED linear R7S 118mm 7.2-60W 830

CorePro R7S is a retrofit replacement for traditional double-ended linear R7S lamps. Its 'light all around' design delivers light just like a halogen lamp. Within the range you can choose dimmable products which have deep dimming function that enables a cozy ambience when using a dimmable fixture.

Product data

General information	
Cap-Base	R7S [R7s]
EU RoHS compliant	Yes
Nominal Lifetime (Nom)	15000 h
Switching Cycle	8000X
Flux measurement reference	Sphere
Light technical	
Color Code	830 [CCT of 3000K]
Luminous Flux (Nom)	810 lm
Color Designation	White (WH)
Correlated Color Temperature (Nom)	3000 K
Luminous Efficacy (rated) (Nom)	112.00 lm/W
Color Consistency	<6
Color Rendering Index (Nom)	80
LLMF At End Of Nominal Lifetime (Nom)	70 %
Operating and electrical	
Input Frequency	50 to 60 Hz
Power (Nom)	7.2 W
Lamp Current (Nom)	40 mA
Wattage Equivalent	60 W
Starting Time (Nom)	0.5 s


Warm Up Time to 60% Light (Nom)	0.5 s
Power Factor (Nom)	0.5
Voltage (Nom)	220-240 V
Temperature	
T-Case Maximum (Nom)	110 °C
Controls and dimming	
Dimmable	No
Mechanical and housing	
Bulb Finish	Clear
Bulb Shape	Linear
Approval and application	
Energy Efficiency Class	E
Suitable For Accent Lighting	No
Energy Consumption kWh/1000 h	8 kWh
EPREL Registration Number	624213
Product data	
Full product code	871951430397300
Order product name	CorePro LED linear R7S 118mm 7.2-60W 830

CorePro LEDlinear MV

EAN/UPC - Product	8719514303973
Order code	929002495002
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	10

Material Nr. (12NC)	929002495002
Net Weight (Piece)	0.016 kg



Dimensional drawing



Product	D	C
CorePro LED linear R7S 118mm 7.2-60W 830	15 mm	118 mm


CorePro LED linear R7S 118mm 7.2-60W 830

Photometric data



LEDlinear CorePro 7,2W R7S 830-LDD

LEDlinear CorePro 7,2W R7S 830-POC





© 2022 Philips Lighting B.V. Page 11

LEDlinear CorePro 7,2W R7S 830-GUL

CorePro LEDlinear MV

Lifetime



Life Expectancy Diagram

Lumen Maintenance Diagram

